

LAND CORNER RECORD

Index: R-8	Corner: E 1/16 Corner between Sections 20 and 29	State of Indiana - Hoosier National Forest
Section: 29	Township: 7N Range: 1E P.M.: 2nd	County: Monroe
Coordinate:	Lat./N: 1374372.43 Long./E: 3138708.02	Datum: NAD83 IN West Zone, US Survey Feet


CORNER HISTORY: (Chronological history of corner)

1.) Date of Survey:	Surveyor:	Monument:	Recording Information:	Monument Photograph:
11/23/2004	Robert Stone USFS Survey Tech	3" Iron pipe with a 3" stamped brass cap found 17" above grade	USDA Forest Service Bedford, IN	
Reference Objects:	Species:	Diameter:	Bearing:	Distance:
	Maple*	13"	S11°W	17.20'
	Maple*	8"	S61°W	24.90'
* = not marked				
Record evidence of prior survey:				
2.) Date of Survey:	Surveyor:	Monument:	Recording Information:	
Reference Objects:	Species:	Diameter:	Bearing:	Distance:
Record evidence of prior survey:				

ACCESSORIES: Bearing and distance from monument to witness object.

Reference Objects:	Object or Tree Species:	Diameter:	Bearing:	Distance:
	Sugar Maple	9"	S66°W	24.50'
	Pignut Hickory*	9"	N36°E	6.70'
	Beech	13"	S35°E	57.15' (slope)
* = tag only				
Monument Found or Set:	A 3" iron pipe with a 3" brass cap stamped "T7N R1E E1/16 S.20 S.29 1978 S0143" was found 1.0' above grade.			


MONUMENT SKETCH



NARRATIVE REFERENCE:

Monument is a 3" iron pipe with a 3" brass cap stamped "T7N R1E E1/16 S.20 S.29 1978 S0143" found 1.0' above grade, a carsonite post is located east 1.5' of the monument, located on the north bank of a southeast-northwest flowing creek, +/- 10' to the centerline of the creek, at the base of a steep slope to the south, 7' south of fence remains, +/- 25' southwest of a 12'X24' outbuilding, +/- 500' west is Roberts Road, S40°E +/- 400' of a house, sloped field to the north, mature forest to the west, south and east, a large rock cairn at the base of the monument.

SECTION DIAGRAM



Corner Location = ●

PERPETUATION RECORD:

The record monument was found undisturbed and maintained by remarking one existing bearing tree and establishing two new bearing trees. One existing bearing tree was recovered from Land Corner Record by Robert Stone, dated 11/23/2004.

Two bearing trees were marked with a blaze, scribed B.T., bearing tree sign, paint, and mag nail. One bearing tree was marked with a tag only.

*Referenced on BRCJ survey recorded as InstNo.2018004725
Accepted by the Monroe County Surveyor Review Board on August 6, 2019.*

Section: 29 T7N R1E

Prepared By: BRCJ (Project#3-0820) Date: 2/2018

Index: R-8	Corner: E-1/16	LAND CORNER RECORD		State of Indiana Hoosier National Forest	
Twtnshp: 7N	Range: 1E	Section: 20/21	2nd P.M.	County: Monroe	
EXISTING SURVEYS					
Original Government Survey			Original Survey Evidence Found		
Year Surveyed:	By:		Date of Search:	By:	
Original Monument:			Monument Found:		
Species	Diameter	Bearing	Distance	Species	Diameter
Subsequent Corner Restoration			Evidence of Subsequent Corner Restoration Found		
Where Filed or Recorded:	Date:		Year Searched:	11/10/04	By: B.Stone
Book:	Page:		Monument Found	3" diameter steel pipe with a 3" diameter brass cap standing 17" above ground and stamped as shown:	
Monument Set:					
Species	Diameter	Bearing	Distance	Species	Diameter

OTHER EVIDENCE

Describe corner loc. Relative to nearby features & dir. To corner location; note fences, roads, etc.	Sketch of Monument
The monument is located on the north bank of a southeast to northwest flowing small stream. It has a 3 foot diameter, 1 foot tall rock cairn built around it. A 8" Hickory with barbwire fence is N 35°E 6.8 feet. A 6' x 12' wooden chicken house with a 12' x 24' fenced coup is approximately 25 feet northeast. The barbwire fence northeast of the monument runs parallel with a stream approximately 80 feet. Approximately 35 feet east of the monument the fence gradually bends to the north. East of the monument are miscellaneous items including a fiberglass truck cap sitting on top of wood pallets next to the fence. Roberts Road can be seen N 70°W approximately 500 feet. Red metal and brown wooden buildings are in the same direction but east of Roberts Road.	

PERPETUATION RECORD

Monument: Describe new monument set or work done to perpetuate/preserve the existing monument/position.	
	
	

Corner Diagram		Accessories: Describe new BTs & witness objects established to perpetuate existing evidence.	
		Maple (no tag, old blaze) 13" S 11°W 17.2 Ft.	Maple (old blaze, no tag) 8" S 61°W 24.9 Ft.
		Corner Recordation:	Certificate Prepared:
		Filed and Recorded in County records:	Date:
		Book:	Page:
Section: 20		Geodetic Coordinates:	Lat./N. Long./E.
		Edited By: Robert J. Stone	Date Created: 11/23/04